



# Resilient Flooring

Wear Layer

# Resilient Flooring

The Continental clear wear layer is formulated and manufactured to provide excellent dimensional stability, industry-leading consistency in appearance and to readily bond to PVC print layers. This industry-approved construction is free of mercury, lead, and cadmium, and this product is formulated without orthophthalate plasticizers.

## Product Overview


<b>Description</b>	PVC clear compact sheet
<b>Applications</b>	Luxury Vinyl Tile Wear Layer
<b>Processing</b>	Heat Lamination

## Dimensional, Color & Weight Properties

<b>Thickness</b>	5-40 mil (0.13- 1.0 mm)
<b>Density</b>	1.29 g/cm <sup>3</sup> (nominal)
<b>Area Weight</b>	650 g/m <sup>2</sup> * (nominal for 20 mil construction)
<b>Width</b>	various, up to 84.25 inches (2140 mm)

## Physical Properties

<b>Thickness</b>	Target +/- 0.001"	ASTM D1777
<b>Width</b>	Target +/- 0.25" up to 84.25" (2140 mm)	ASTM D882
<b>Hardness</b>	48 (nominal)	ASTM D2240
<b>Dimensional Stability</b>	<4%	ASTM D1204
<b>Color/Appearance</b>	Natural (clear)	Visual
<b>Yellowness Index</b>	<1.25 for 5 mil (thickness dependent)	Spectrophotometer
<b>Plasticizer Content</b>	REACH & CA Prop 65 Compliant	GC/MS



Properties listed do not constitute a warranty or specification. Test values are based on material conditioned and tested in a controlled laboratory using established standards and procedures. Properties vary based on embossed grain, color, multi-ply lamination and other variables.

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2019 ContiTech AG. All rights reserved. For complete information go to: [www.contitech.de/discl\\_en](http://www.contitech.de/discl_en)

