

Cementing Hose

STANDARD

API Spec. 7K FSL 0

CONSTRUCTION

Bore type

full flow, smooth bore

Liner material

NBR

Operating temperature

-13°F to 212°F (-25°C to 100°C)

Max. available length

60m (200 ft)

FEATURES & COMMENTS

- › Hoses with a temperature rating of -22°F to 250°F (-30°C to 121°C) and -40°F to 180°F (-40°C to 82°C) are available upon request



TECHNICAL DATA

Inside Diameter		Rated Working Pressure		Test Pressure		Safety Factor	Outer Diameter		MBR (storage)		MBR (operation)		Weight	
mm	in.	bar	psi	bar	psi	WP	mm	in.	m	ft.	m	ft.	kg/m	lb./ft.
54	2.0	345	5,000	690	10,000	2.5	72	2.83	0.6	1.97	0.6	1.97	15	10.0
							104	4.09	0.6	1.97	0.7	2.30		
		690	10,000	1,035	15,000	2.25	72	2.83	0.6	1.97	0.6	1.97	27	18.1
							123	4.84	0.9	2.95	1.0	3.28		
64	2.5	345	5,000	690	10,000	2.5	111	4.37	0.6	1.97	0.7	2.30	15	10.1
							136	5.35	1.0	3.28	1.1	3.61		
		1,035	15,000	1,552	22,500	2.25	153	6.02	1.2	3.94	1.5	4.92	45	30.2
							166	6.54	1.4	4.59	1.6	5.25		
76	3.0	345	5,000	690	10,000	2.5	126	4.96	0.7	2.30	0.8	2.62	18	12.1
							148	5.83	1.1	3.61	1.2	3.94		
		1,035	15,000	1,552	22,500	2.25	166	6.54	1.4	4.59	1.6	5.25	53	35.6
							210	8.27	1.6	5.25	1.6	5.25		
102	4.0	345	5,000	517	7,500	2.25	166	6.54	1.0	3.28	1.2	3.94	33	22.2
							192	7.56	1.5	4.92	1.7	5.58		
		1,035	15,000	1,552	22,500	2.25	222	8.74	1.4	4.59	1.4	4.59	108	72.6