

Flexible Choke & Kill Line with Tauroflon™ liner (up to 266°F/130°C)



STANDARD

API Spec. 16C up to FSL 3

CONSTRUCTION

Bore type

Full flow, rough bore

Liner material

H₂S resistant Tauroflon™

Operating temperature

-4°F to 266°F (-20°C to 130°C)

Survival temperature

350°F (177°C) for at least 1 hour

Max. available length

60m (200 ft)



FEATURES & COMMENTS

- › Suitable for well completion
- › Coupling materials meet NACE MR 01-75 / ISO 15156 latest edition
- › See Flexible Tauro™Fit Choke & Kill Lines for subsea BOPs and for Flexible Choke & Kill Lines with extremely small MBRs
- › See Well Test Hoses for well test applications
- › Saudi Aramco approved

TECHNICAL DATA

Inside Diameter		Type	Rated Working Pressure		Test Pressure		Safety Factor	Outer Diameter		MBR (storage)		MBR (dynamic)		Weight	
mm	in.		bar	psi	bar	psi		WP	mm	in.	m	ft.	m	ft.	kg/m
54	2.0	Fire rated	345	5,000	517	7,500	2.25	159	6.26	0.9	2.95	0.9	2.95	46	30.9
		Fire rated c/w st. st. wrap						165	6.50	0.9	2.95	0.9	2.95	52	34.9
		Fire rated	690	10,000	1,035	15,000	2.25	159	6.26	0.8	2.62	0.8	2.62	46	30.9
		Fire rated c/w st. st. wrap						165	6.50	0.8	2.62	0.8	2.62	52	34.9
		Fire rated	1,035	15,000	1,552	22,500	2.25	188	7.40	0.8	2.62	0.8	2.62	79	53.1
		Fire rated c/w st. st. wrap						194	7.64	0.8	2.62	0.8	2.62	86	57.8
		Standard	1,380	20,000	2,070	30,000	2.25	201	7.91	0.9	2.95	0.9	2.95	92.2	62.0
		Standard c/w st. st. wrap					207	8.15	0.9	2.95	0.9	2.95	99.8	67.1	
65	2.5	Fire rated	345	5,000	517	7,500	2.25	172	6.77	1.0	3.28	1.0	3.28	52	34.9
		Fire rated c/w st. st. wrap						178	7.01	1.0	3.28	1.0	3.28	59	39.6
		Fire rated	690	10,000	1,035	15,000	2.25	172	6.77	1.0	3.28	1.0	3.28	52	34.9
		Fire rated c/w st. st. wrap						178	7.01	1.0	3.28	1.0	3.28	59	39.6
		Fire rated	1,035	15,000	1,552	22,500	2.25	202	7.95	0.9	2.95	0.9	2.95	88	59.1
		Fire rated c/w st. st. wrap						207	8.15	0.9	2.95	0.9	2.95	96	64.5
		Standard	1,380	20,000	2,070	30,000	2.25	211	8.31	1.1	3.61	1.1	3.61	99.1	66.6
		Standard c/w st. st. wrap					217	8.54	1.1	3.61	1.1	3.61	107	71.9	
78	3.0	Fire rated	345	5,000	517	7,500	2.25	202	7.95	1.0	3.28	1.0	3.28	88	59.1
		Fire rated c/w st. st. wrap						207	8.15	1.0	3.28	1.0	3.28	96	64.5
		Fire rated	690	10,000	1,035	15,000	2.25	202	7.95	1.0	3.28	1.0	3.28	88	59.1
		Fire rated c/w st. st. wrap						207	8.15	1.0	3.28	1.0	3.28	96	64.5
		Fire rated	1,035	15,000	1,552	22,500	2.25	218	8.58	1.0	3.28	1.0	3.28	103	69.2
		Fire rated c/w st. st. wrap						223	8.78	1.0	3.28	1.0	3.28	111	74.6
		Standard	1,380	20,000	2,070	30,000	2.25	231	9.09	1.2	3.94	1.2	3.94	118	79.3
		Standard c/w st. st. wrap					237	9.33	1.2	3.94	1.2	3.94	126.6	85.1	
104	4.0	Fire rated	345	5,000	517	7,500	2.25	237	9.33	1.5	4.92	1.5	4.92	104	69.9
		Fire rated c/w st. st. wrap						243	9.57	1.5	4.92	1.5	4.92	112	75.3
		Fire rated	690	10,000	1,035	15,000	2.25	237	9.33	1.5	4.92	1.5	4.92	104	69.9
		Fire rated c/w st. st. wrap						243	9.57	1.5	4.92	1.5	4.92	112	75.3