

CONTI-AIR® STEEL UV Black SP

Metalback Blanket for UV based Inks



CONTI-AIR® STEEL UV Black SP

The metalback blanket for Packaging, Label and Security Applications


- > Developed for UV-curing Inks
- > Medium to hard blanket construction
- > Neutral Feeding Characteristic (within CA MBB Range)
- > Developed for highest durabilty
- > Using the special CONTI-AIR® microcell technology

Guiding Value

| | | Standard |
|----------------------------|--------------------------------------|--------------------|
| Color: | black | |
| Surface: | ground | |
| Hardness of face compound: | approx. 63 Shore A | DIN ISO 48-4*/** |
| Thickness: | according to OEM drawing | DIN EN ISO 2286-3* |
| Metal base: | steel | |
| Backside: | calibrated film (only when required) | |

Unsere Drucktücher verfügen über eine spezielle CONTI-AIR® kompressible Schicht geschlossener Mikrozellen mit Überdruck.

Our printing blankets have a special CONTI-AIR® compressible layer of over pressured microcells.







ContiTech Elastomer-Beschichtungen GmbH

Breslauer Str. 14 | 37154 Northeim | Germany service@contiair.com https://www.continental-industry.com/conti-air The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2025 Contifech AG, Hanover. All rights reserved. For complete information go to: www.continental-industry.com/discl_en Der Inhalt dieser Druckschrift ist unverbindlich und dient ausschließlich Informationszwecken Für weitere Information besuchen Sie bitte: www.continental-industry.com/discl_de



^{*} Average value obtained in accordance with the given standard. Please note that the number of samples tested may differ
** The specified hardness of the cover compound can only be measured using test samples according to the standard. It is not possible to measure the hardness directly on the product itself