

## Conti Repair 60SLF

- › 2-Component urethane material
- › Dual tube with automatic blending
- › No guesswork or messy measuring
- › Repair, bond, & seal virtually any surface
- › Fast setting
- › Minimized downtime
- › No solvents or VOCs
- › No odors
- › No shrinkage
- › Hot-Cold resistant
- › No drip
- › Can sand, grind, paint, drill & tap



### Your Answer For:

#### **Conveyor Belt Repair**

Textile & Steel Cable belts, PVC & Urethane Belts, Belt Lacing, Clip Covering

#### **Elastomeric Repair**

Rubber Linings, Urethane Linings, Off-Road & Forklift Tires, Pulley Lagging, Pump Liners

#### **Concrete Repair**

Floors, Containments, Walls, Cracks, Spalling, Threading & Mounting

### Storage and Shelf-Life:

Store products between 15°C to 25°C (60°F to 70°F). Keep in a dry, well ventilated location away from direct sunlight and ignition source. When stored properly, the shelf life is 3 years unopened.

Products manufactured by Normac Adhesive Products, Inc. per Continental Specifications.

Copyright © 2023 ContiTech AG. All rights reserved. For complete information go to: [www.continental-industry.com/discl\\_en](http://www.continental-industry.com/discl_en)



**Continental**

[www.continental-industry.com](http://www.continental-industry.com)