

**Vulcan Advance**  
Heatset

# Vulcan Advance




**Main Application**  
Heatset

**Advantages of the product**

- › Top surface for hybrid applications
- › Neutral paper feed
- › Very robust and stable carcass
- › Suitable for printing on low grams paper

**Vulcan Advance is available in 4ply, 1,95 mm thickness**



**Guiding Value**

**Standard**

<b>Color:</b>	Green	
<b>Structure:</b>	4 ply	
<b>Surface Roughness Ra*:</b>	1,1 micron	IO LAB TEC 060 - E (internal)
<b>Compressibility @ 0,23 mm*:</b>	2,6 MPa	IO LAB TEC 060 - B (internal)
<b>Thickness +/-0,02 mm*:</b>	1,95 mm	IO LAB TEC 060 - C (internal)

\* Average value obtained in accordance with the given standard. Please note that the number of samples tested may differ.



**Continental Coated Systems Italy S.p.A**  
Strada Provinciale 140,  
26855 Lodi Vecchio, Italy  
[www.continental-industry.com/printing-technology](http://www.continental-industry.com/printing-technology)

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2024 ContiTech Deutschland GmbH, Hannover. All rights reserved. For complete information go to: [www.continental-industry.com/disco\\_en](http://www.continental-industry.com/disco_en)