

# Printec 2115 PRO/2135 PRO

Coating



### Printec 2115 PRO/2135 PRO



#### **Main Application**

Coating

#### **Advantages of the product**

- Polymer coating plate with excellent resistance to UV and Aqueous coatings
- > Excellent dimensional stability thanks to the polyester carrier
- > Very good stripping with clear and visible cut lines
- > Usable in both directions thanks to its fabricless design

## Printec 2115 PRO/2135 PRO is available in 1,15 - 1,35 mm thickness



#### **Guiding Value**

		Standard
Color:	Grey	
Structure:	Fabricless	
Surface Roughness Ra*:	0,5 micron	IO LAB TEC 060 - E (internal)
Compressibility @ 0,23 mm*:	N/A	IO LAB TEC 060 - B (internal)
Thickness +/-0,05 mm*:	1,15 - 1,35 mm	IO LAB TEC 060 - C (internal)
Cutting depth*:	0,8 - 1,0 mm	IO LAB TEC 060 - C (internal)

<sup>\*</sup> Average value obtained in accordance with the given standard. Please note that the number of samples tested may differ.



Continental Coated Systems Italy S.p.A Strada Provinciale 140, 26855 Lodi Vecchio, Italy www.continental-industry.com/printing-technology The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2024 Contifech Deutschland GmbH, Hannover All rights reserved. For complete information go to: www.continental-industry.com/discl\_en

