



CONTI ALLCRETE® PRO WIRE - 130BAR

High quality for high pressure concrete lines



MARKING: 3 orange axially applied stripes on black cover "Continental ALLCRETE® PRO WIRE DN 125 (5") - 130 BAR (1885 PSI) - SF2 - 40,0kg/m (26,9lbs/ft) "

APPLICATIONS

Concrete and soil pumps

FLOW MEDIUM

Concrete

DESCRIPTION

Inner lining: Special elastomer, black, highly abrasion resistant (acc. to DIN ISO 4649-A: <90mm³), homogenous, smooth

Reinforcements: high tension steel wire

Cover: Spezial elastomer, black, fabric patterned, abrasion resistant, resistant to ozone, weather and UV

Working pressure up to: 130 bar / 1885 psi

Temperature range: from -40 °C / -40 °F up to +65 °C / +149 °F

Further properties: Available flange systems: Victaulic, Heavy Duty (US), etc.

Couplings are partly hardened and with galvanized sleeve

Fixed lengths with built-in couplings acc. to customers request

TECHNICAL DATA

nominal width	inner-Ø	wall thickness	outer-Ø	length	working pressure	min. burst pressure	vacuum	min. bending radius	weight
Zoll/inch	mm	mm	mm	m	bar	psi	bar	mm	aprx. g/ m
5	125	15	155	40	130	1885	-0.8	1250	11500

Pressure and vacuum based on room temperature / High pressure and/or temperature lead to reduced component durability