




CONTI[®] CEMENT SILO

The reliable specialist



MARKING: 3 orange, axially applied stripes on black cover " Continental CEMENT SILO DN 75 PN 6 BAR / 87 PSI Made in Germany"

APPLICATIONS

Building material stores, Cement plants, Cement silo trucks,
Forwarding agents

FLOW MEDIUM

Cement, Concrete, Gravel, Sand

DESCRIPTION

- Inner lining:** SBR, black, highly abrasion resistant, non-porous, smooth
- Reinforcements:** Synthetic fibres
With copper wire
- Cover:** SBR, black, fabric patterned, abrasion resistant, resistant to ozone, weather and UV
- Working pressure up to:** 6 bar / 87 psi
- Temperature range:** from -20 °C / -4 °F up to +70 °C / +158 °F
- Further properties:** Electrically conductive, $R < 10^6 \Omega/m$

TECHNICAL DATA

nominal width	inner-Ø	wall thickness	outer-Ø	length	working pressure		min. burst pressure		min. bending radius	weight
zoll/inch	mm	mm	mm	m	bar	psi	bar	psi	aprx. mm	aprx. g/ m
2	50	9	68	40	6	87	18	261	500	1980
3	75	9	93	40	6	87	18	261	750	2770
4	100	10	120	40	6	87	18	261	1000	4020

Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability / Other dimensions on request