



CONTI® FIRE HOSE CO₂

A high degree of safety



MARKING:

APPLICATIONS

Fire extinguisher

FLOW MEDIUM

Extinguishing media

DESCRIPTION

Inner lining: SBR-EPDM, black, non-porous, smooth

Reinforcements: Synthetic fibres

Cover: SBR-EPDM, black, smooth, abrasion resistant, resistant to ozone, weather and UV

Working pressure up to: 30 bar / 435 psi

Temperature range: from -30 °C / -22 °F up to +80 °C / +176 °F

Further properties: Electrically conductive, $R < 10^8 \Omega$
Suitable for commercial portable fire extinguisher

TECHNICAL DATA

nominal width	inner-Ø	wall thickness	outer-Ø	length	working pressure		min. burst pressure		min. bending radius	weight
zoll/inch	mm	mm	mm	m	bar	psi	bar	psi	aprx. mm	aprx. g/ m
3/8	10	3	16	40	30	435	90	1305	100	170
3/8	10	3	16	80	30	435	90	1305	100	170
1/2	13,2	3,75	20,7	40	30	435	90	1305	132	270
1/2	13,2	3,75	20,7	80	30	435	90	1305	132	270

Pressure data relate to room temperature / High pressures and/or temperatures reduce the service life