



CONTI® FUEL CKR 2162

Fuel hose conductive - stainless steel braided



MARKING: Dimension-> FPM/HNBR/CSM < W/J/TC

APPLICATIONS

Diesel fuel pipes

FLOW MEDIUM

Biodiesel resistant, Diesel fuel, Fuel

DESCRIPTION

- Inner lining:** FPM/HNBR, black
- Reinforcements:** Aramid
- Cover:** CSM, black, grooved
- Working pressure up to:** 35 bar / 508 psi
- Temperature range:** from -40 °C / -40 °F up to +125 °C / +257 °F
up to +150 °C / +302 °F
- Further properties:** Electrically conductive, $R < 10^6 \Omega/m$
Highly flexible
low permeability

TECHNICAL DATA

nominal width zoll/inch	inner-Ø mm	wall thickness mm	outer-Ø mm	length m	working pressure		min. burst pressure		vacuum		min. bending radius aprx. mm	weight aprx. g/ m
					bar	psi	bar	psi	bar	mmHG		
1/4	6	3.5	13	20	25	363	125	1813	-0.92		70	233
5/16	8	3.5	15	20	25	363	125	1813			80	283
3/8	10	3.5	17	20	25	363	125	1813			80	333
1/2	12	3.5	19	20	25	363	125	1813			100	369
5/8	15	4	23	20	35	508	175	2538			110	496

Pressure and vacuum based on room temperature / High pressure and/or temperature lead to reduced component durability / Other dimensions upon request