



CONTI® FUEL CKR 2167

Fuel hose



LABEL: Abmessung- >FKM/ECO/AR/AEM< W/J/TC

FLOW MEDIUM

Biodiesel resistant, Diesel fuel

DESCRIPTION

Inner lining:	FPM/ECO, black
Reinforcements:	Aramid
Cover:	AEM, black, smooth
Working pressure up to:	10 bar / 145 psi
Temperature range:	from -40 °C / -40 °F up to +150 °C / +302 °F up to +175 °C / +347 °F
Further properties:	Highly flexible low permeability

TECHNICAL DATA

nominal width zoll/inch	inner-Ø mm	wall thickness mm	outer-Ø mm	length m	helix helix	working pressure		min. burst pressure		min. bending radius aprx. mm	weight aprx. g/ m
						bar	psi	bar	psi		
1/4	5.5	3	11.5	80	●	10	145	70	1015	60	120
5/16	7.5	3.5	14.5	80	●	10	145	70	1015	70	165

Pressure and vacuum based on room temperature / High pressure and/or temperature lead to reduced component durability / Other dimensions upon request

Industrial Fluid Solutions

ContiTech Schlauch GmbH
Continentalstr. 3-5 | 34497 Korbach, Germany
industrialhoses@fluid.contitech.de

Version: 2021_05.16 | 2021-05-31

www.continental-industry.com

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2021 ContiTech AG. All rights reserved. For complete information go to: www.continental-industry.com/en/special-pages/disclaimer-publications