



CONTI® PAINT SPRAY HOSE PA

The reliable specialist



MARKING: on a grey background "Continental FARBSPRITZ / PAINT SPRAY PA DN 9 PN 25 BAR / 363 PSI R < 10²Ω Typ M Made in Germany"

FLOW MEDIUM

Glues, Lacquers, Oils, Paints, Polar and aromatic solvents

STANDARD / APPROVAL

TRBS

2153

DESCRIPTION

- Inner lining:** PA, black, highly abrasion resistant, non-porous, smooth
- Reinforcements:** Synthetic fibres
- Cover:** NBR, grey, resistant to ozone, weather and UV
- Working pressure up to:** 25 bar / 363 psi
- Temperature range:** from -25 °C / -13 °F up to +80 °C / +176 °F
- Further properties:** Length independently electrically conductive, R < 10² Ω

TECHNICAL DATA

nominal width	inner-Ø	wall thickness	outer-Ø	length	working pressure		min. burst pressure		min. bending radius	weight
zoll/inch	mm	mm	mm	m	bar	psi	bar	psi	aprx. mm	aprx. g/ m
1/4	6	2,5	11	> 10	25	363	100	1450	60	86
1/3	8	3	14	> 10	25	363	100	1450	80	140
3/8	9	3,5	16	> 10	25	363	100	1450	90	184
7/16	11	4	19	> 10	25	363	100	1450	110	243
1/2	13	4	21	> 10	25	363	100	1450	130	240

Pressure data relate to room temperature / High pressures and/or temperatures reduce the service life