




CONTI® PREMIUM SUCTION SD

Suction hose for sewer cleaning suitable for all reel types



MARKING: 3 orange, axially applied stripes on black cover "Continental PREMIUM SUCTION SD DN 100 PN 6 BAR / 87 PSI Made in Germany" "Continental PREMIUM SUCTION SD DN 100 PN 6 BAR / 87 PSI Made in Germany"

APPLICATIONS

Sewer cleaning vehicles

FLOW MEDIUM

Abrasive bulk material, Water

DESCRIPTION

- Inner lining:** SBR-BR, black, highly abrasion resistant, homogenous, seamless, smooth
- Reinforcements:** Synthetic fibres
With integrated steel wire helix
- Cover:** SBR-BR, black, fabric patterned, abrasion resistant, resistant to ozone, weather and UV
- Working pressure up to:** 6 bar / 87 psi
- Temperature range:** from -40 °C / -40 °F up to +80 °C / +176 °F
- Further properties:** Electrically conductive, $R < 10^6 \Omega/m$
Long-lasting

TECHNICAL DATA

nominal width	inner-Ø	wall thickness	outer-Ø	length	helix	working pressure		min. burst pressure		vacuum		min. bending radius	weight
zoll/inch	mm	mm	mm	m	helix	bar	psi	bar	psi	bar	mmHG	aprx. mm	aprx. g/ m
4	100	8	116	20	●	6	87	15	218	-0.9	-675	400	4300
5	125	10	145	20	●	6	87	15	218	-0.9	-675	500	6300
6	150	11	172	20	●	6	87	15	218	-0.9	-675	600	8100

Pressure and vacuum based on room temperature / High pressure and/or temperature lead to reduced component durability