

PAGUCLAMP® FITTING SYSTEM

The ideal half-shell fitting for the beverage and food industry



APPLICATIONS

Foodstuff industry, Milk processing industry, Other installations in the brewing, beverage and spirits industry

DESCRIPTION

Working pressure up to:	16 bar / 232 psi					
Further properties:	1 set consisting of 2 half shells, 4 screws and 4 nuts					
	For hoses with helix, use a reduced nozzle!					
	Material: stainless steel					
	No damage to lining through swaging process					
	Optimally adapted to $PAGUFIX^{\texttt{s}}$ nozzles due to the coordinated tooth geometry					
	Reusable					
	Rubber protection rings available in blue					

Smooth and hygienically clean connection, without any transition between lining and fitting

Very high compression strength and resistance to to pull-off forces, also with hot cleaning through ideal tooth geometry

TECHNICAL DATA

nominal width	inner-Ø mm	wall thickness	outer-Ø mm	working pressure		min. burst pressure		weight
zoll/inch				bar	psi	bar	psi	aprx. g/ St
1/2	13	4	21	16	232	48	696	181
3/4	19	5	29	16	232	48	696	222
1	25	6	37	16	232	48	696	402
1 1/4	32	6	44	16	232	48	696	436
1 1/4	32	8	48	16	232	48	696	464
1 1/2	38	6.5	51	16	232	48	696	521
1 1/2	38	9	56	16	232	48	696	580
1 2/3	40	7	54	16	232	48	696	580
1 2/3	40	9	58	16	232	48	696	615
2	50	8	66	16	232	48	696	727
2	50	10	70	16	232	48	696	814
2 1/2	63	7.5	78	16	232	48	696	1060
2 5/8	65	8	81	16	232	48	696	1972
2 5/8	65	12	89	16	232	48	696	1149
3	75	8	91	16	232	48	696	1349
3	75	12	99	16	232	48	696	1648
3 1/8	80	8	96	16	232	48	696	1540
3 1/8	80	14	108	16	232	48	696	1814
4	100	9	118	16	232	48	696	2065
4	100	15	130	16	232	48	696	2163

Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability

Industrial Fluid Solutions

ContiTech Schlauch GmbH Continentalstr. 3-5 | 34497 Korbach, Germany

IFS IH - Version: 2021 12.117 | 2023-09-14

www.continental-industry.com

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2023 ContiTech Deutschland GmbH. All rights reserved. For complete information go to: www.continental-industry.com/en.