



PARKING



MARKING: 6 blue stripes on black cover

APPLICATIONS

Compressed air and compressor manufacturers, Largescale garages, Over- and underground workings, Petrol stations, Quarry, Shipyards, Steel and iron industry

FLOW MEDIUM

Compressed air, Pressurized air

DESCRIPTION

Inner lining: SBR, black, non-porous, smooth

Reinforcements: Synthetic fibres

Cover: SBR-EPDM, black, smooth

Working pressure up to: 20 bar / 290 psi

Temperature range: from -20 °C / -4 °F up to +65 °C / +149 °F

Further properties: Suitable for hot water for a short time up to +80°C / +176°F

TECHNICAL DATA

nominal width	inner-Ø	wall thickness	outer-Ø	length	working pressure		min. burst pressure		min. bending radius	weight
Zoll/inch	mm	mm	mm	m	bar	psi	bar	psi	aprx. mm	aprx. g/ m
1/4	6	3,5	13	25	20	290	60	870	60	170
1/4	6	3,5	13	50	20	290	60	870	60	170
1/3	8	3,5	15	25	20	290	60	870	80	200
1/3	8	3,5	15	50	20	290	60	870	80	200
3/8	10	3,5	17	25	20	290	60	870	100	250
3/8	10	3,5	17	50	20	290	60	870	100	250
1/2	13	4,3	21,6	40	20	290	60	870	130	350
1/2	13	4,3	21,6	20	20	290	60	870	130	350
3/4	19	5,5	30	40	20	290	60	870	190	580
3/4	19	5,5	30	20	20	290	60	870	190	580

Temperature resistance applies only to materials used / All technical data apply at room temperature