



**©ntinental** PHX AUTOGEN 6,3 x 13,3 DIN EN ISO 3821 2MPa

MARKING: on blue cover "Continental PHX AUTOGEN DN 6,3 x 13,3 DIN EN ISO 3821 2MPa (20 BAR / 290 PSI) Made in Germany"

## **APPLICATIONS**

Automobile industry, Installation and heating system companies, Over- and underground workings, Steel construction, Welding shops

## **FLOW MEDIUM**

Oxygen

## STANDARD / APPROVAL

DIN EN ISO

## **DESCRIPTION**

Inner lining: SBR, black, non-porous, smooth

**Reinforcements:** Synthetic fibres

**Cover:** SBR, blue, smooth, abrasion resistant, resistant to ozone, weather

and UV

Working pressure up 20 bar / 290 psi

to:

**Temperature range:** up to +60 °C / +140 °F **Further properties:** Dimensionally stable

Flexible Kink-resistant

Release agent- and fat free, free from product harmful to lacquer

Robust

# **TECHNICAL DATA**

nominal width	inner-Ø	wall thickness	outer-Ø	length	working pressure		min. burst pressure		min. bending radius	weight
zoll/inch	mm	mm	mm	m	bar	psi	bar	psi	aprx. mm	aprx. g/ m
1/6	4	3.5	11	40	20	290	60	870	25	130
1/4	6.3	3.5	13.3	40	20	290	60	870	30	170
1/4	6.3	5	16.3	40	20	290	60	870	35	270

Pressure based on room temperature / High pressure and/or temperature lead to reduced component durability

### www.continental-industry.com