



TRIX PAINT SPRAY HOSE EPDM

For simple and safe painting



MARKING: 6 orange, axially applied stripes on a black background "Continental TRIX® FARBSPRITZ / PAINT SPRAY EPDM DN 9 PN 10 BAR / 145 PSI R < 10⁶Ω
Made in Germany"

APPLICATIONS

Coating companies, Painting companies, Shipyards

FLOW MEDIUM

Acetone, Ammonia solution - 25%, Caustic soda - 10%, Chlorine rubber lacquer, Dimethyl sulfoxide, Dimethylformamide, Distempers, Emulsion paints, Ester, Ethyl alcohol, Nitro cellulose lacquer, Polyurethane lacquer, Spirit lacquer, Universal thinner, Water-based paints

DESCRIPTION

Inner lining: EPDM, black, non-porous, smooth

Reinforcements: Synthetic fibres

Cover: EPDM, black, smooth, ozone-resistant

Working pressure up to: 10 bar / 145 psi

Further properties: Length independently electrically conductive, Ω-CL (acc. to EN ISO 8031)

Temperature range: from +5 °C / +41 °F up to +35 °C / +95 °F

TECHNICAL DATA

nominal width zoll/inch	inner-Ø mm	wall thickness mm	outer-Ø mm	length m	working pressure		min. burst pressure		min. bending radius aprx. mm	weight aprx. g/ m
					bar	psi	bar	psi		
3/8	9	3.5	16	40	10	145	40	580	90	230

Temperature resistance applies only to materials used / All technical data apply at room temperature