



## TRIX PAINT SPRAY HOSE NBR

For simple and safe painting



**MARKING:** 6 grey, axially applied stripes on a black background "Continental TRIX® FARBSPRITZ / PAINT SPRAY NBR DN 9 PN 25 BAR / 363 PSI R < 10<sup>6</sup>Ω Made in Germany"

### APPLICATIONS

Coating companies, Painting companies, Shipyards

### FLOW MEDIUM

Ammonia solution - 25%, Benzine, Caustic soda - 10%, Distempers, Emulsion paints, Ethyl alcohol, Polyurethane lacquer, Spirit lacquer, Water, Water-based paints

### DESCRIPTION

**Inner lining:** NBR, black, non-porous, smooth

**Reinforcements:** Synthetic fibres

**Cover:** NBR, black, smooth, ozone-resistant

**Working pressure up to:** 25 bar / 363 psi

**Further properties:** Length independently electrically conductive, Ω-CL (acc. to EN ISO 8031)

Temperature range: from +5 °C / +41 °F up to +35 °C / +95 °F

### TECHNICAL DATA

nominal width	inner-Ø	wall thickness	outer-Ø	length	working pressure		min. burst pressure		min. bending radius	weight
zoll/inch	mm	mm	mm	m	bar	psi	bar	psi	aprx. mm	aprx. g/ m
1/4	6	3.5	13	40	25	363	100	1450	60	170
3/8	9	3.5	16	40	25	363	100	1450	90	230
7/16	11	4	19	40	25	363	100	1450	110	260

Temperature resistance applies only to materials used / All technical data apply at room temperature